

# Dyatic VOC

## Description

*A chemically active material formulated to soften and remove concrete build-up and prevent new build-up on concrete tools, hardware, etc. V.O.C. compliant.*

## Manufacturer

Conspec  
636 S. 66th Terrace  
Kansas City, Kansas 66111  
**Customer Service** (800) 348-7351  
**Technical Service** (877)CONSPEC

## Use

Prevents and removes concrete build-up on concrete forms, tools, mixers, hardware, shoring and scaffolding equipment, ready mix truck chutes, mortar mixers, aluminum forms and post tension rods.

Treat equipment with Dyatic VOC prior to use and again before cleaning or storing.

## Benefits

- V.O.C. compliant - Federal standards
- Softens concrete build-up for easier removal
- Seals steel, aluminum and other alloy metals to prevent concrete bonding

## Application

Lightly spray Dyatic VOC over the interior of concrete mixers after clean out to prevent concrete bonding. Dyatic VOC, over time, will soften and remove hardened concrete. Forming hardware with concrete build-up should be soaked in Dyatic VOC until the build-up becomes soft and easy to remove.

Coat concrete handling equipment such as chutes, shovels, etc. before using to prevent concrete build-up.

Aluminum forms that have developed a scum coat or concrete build-up should receive a moderately heavy coat of Dyatic VOC twenty-four hours before pouring. Repeat until build-up and scum are removed.

Equipment in concrete block plants can be kept free of build-up by spraying a light coat of Dyatic VOC on mixers, hoppers, and chutes.

## Packaging

55 gallon drums  
5 gallon pails  
1 gallon jugs (4 to a case)

## Limitations/Precautions

Combustible...Contains petroleum distillates. Keep out of reach of children. Do not take internally. Do not breathe vapors. Avoid prolonged contact with skin. If swallowed, call physician. If splashed in eyes, wash repeatedly with clean water and call physician. Keep away from heat, sparks and open flame.

*Recommended Safety Equipment:*  
Rubber gloves, goggles and if applied in areas of poor or inadequate ventilation, use mine safety appliances, mask and canister:

*Organic Vapor Mask*

(No. 457081)

*Organic Vapor Canister*

(No. 77705GAM)

*Threshold Limit Value:* 100 PPM.  
Ventilation system should be capable of exchanging total air volume in application area in 30 minutes or less.

Avoid hazards by following all precautions found in the Material Safety Data Sheet (MSDS), product labels and technical literature. Please read this information prior to using the product.

## V.O.C. Content

Less than 450 g/l. Complies with Federal V.O.C. standards for Form Release Agents. Do not thin or dilute.

## Warranty

Conspec warrants, for 12 months from the date of manufacture or for the duration of the published product shelf life, whichever is less, that at the time of shipment by Conspec, the product is free of manufacturing defects and conforms to Conspec's published specifications in force on the date of acceptance by Conspec of the order. Conspec shall only be liable under this warranty if the material has been applied, used, and stored in accordance with Conspec's instructions in this technical data sheet. The purchaser must examine the product when received and promptly notify Conspec in writing of any non-conformity before the product is used, or no later than 30 days after such non-conformity is first discovered. If Conspec, in its sole discretion, determines that the product breached the above warranty, it will, in its sole discretion, replace the non-conforming product, refund the purchase price or issue a credit in the amount of the purchase price. This is the sole and exclusive remedy for breach of this warranty. Only a Conspec

officer is authorized to modify this warranty. The sales information on the Conspec website and received by the customer during the sales process does not supersede this warranty and the specifications of the product in force on the date of sale. THE FOREGOING WARRANTY SHALL BE EXCLUSIVE AND IN LIEU OF ANY OTHER WARRANTY, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND ALL OTHER WARRANTIES OTHERWISE ARISING BY OPERATION OF LAW, COURSE OF DEALING, CUSTOM, TRADE OR OTHERWISE.

### Limitation of Liability

Conspec shall not be liable in contract or in tort (including, without limitation, negligence, strict liability or otherwise) for loss of sales, revenues or profits; cost of capital or funds; business interruption or cost of downtime, loss of use, damage to or loss of use of other property (real or personal); failure to realize expected savings; frustration of economic or business expectations; claims by third parties (other than for bodily injury), or economic losses of any kind; or

for any special, incidental, indirect, consequential, punitive or exemplary damages arising in any way out of the performance of, or failure to perform, this Agreement, even if Conspec could foresee or has been advised of the possibility of such damages. The Parties expressly agree that these limitations on damages are allocations of risk constituting, in part, the consideration for this agreement, and also that such limitations shall survive the determination of any court of competent jurisdiction that any remedy provided in these terms or available at law fails of its essential purpose.

## Storage

Dyatic VOC should be stored in tightly sealed original factory containers. Store in a horizontal position to prevent moisture accumulation on the drum head.

## Technical Services

Complete technical and specification services are available from the manufacturer and their authorized representatives and distributors.

## Filing System

Additional literature and the Material Safety Data Sheet can be obtained from Conspec upon request.