

**Product Data Sheet**  
Edition 5.16.2006  
Identification no.  
Sikagard High Gloss Sealer

## Sikagard® High Gloss Sealer

<b>Description</b>	Sikagard High Gloss Sealer is an acrylic concrete and masonry sealer.
<b>Where To Use</b>	Sikagard High Gloss Sealer seals concrete and masonry surfaces, such as sidewalks, steps, patios, porches, garages, driveways, basement floors, and brick against moisture, de-icing salts, and other harmful chemicals.
<b>Advantages</b>	<ul style="list-style-type: none"><li>■ Helps control dusting.</li><li>■ Provides protection from mild corrosives.</li></ul>
<b>Coverage</b>	1 gallon covers approximately 400 sq. ft.
<b>Packaging</b>	1 gallon jug
<b>How to Use</b>	
<b>Surface Preparation</b>	Surfaces must be clean and sound. Remove all dust, dirt, loose concrete, grease, curing compounds, paint and other particles.
<b>Priming</b>	All porous areas or concrete with excessive porosity or chalky surfaces should be primed using Sikagard 552W or SikaLatex R to allow easy application of Sikagard Elastic Base Coat.
<b>Mixing</b>	Shake product thoroughly before applying.
<b>Application</b>	Sikagard High Gloss Sealer can be applied by sprayer, brush or roller. Apply over the entire area moving in one direction. Additional coats can be applied for higher gloss. Wait one day before exposing to foot/car traffic.
<b>Limitations</b>	<ul style="list-style-type: none"><li>■ Substrate must be dry prior to application.</li><li>■ Protect from freezing.</li><li>■ Do not store in direct sunlight.</li><li>■ Do not apply if rain is in the forecast.</li><li>■ Concrete must be at least 14 days old.</li><li>■ Do not use over moving cracks.</li><li>■ Do not thin product.</li><li>■ Read technical data sheet prior to use.</li></ul>

### Typical Data (Material and curing conditions at 73°F (23°C) and 50% R.H.)

<b>Shelf Life</b>	1 year
<b>Storage Conditions</b>	Store dry at 45-90°F. Keep from freezing.
<b>Color</b>	Clear

The Sika logo consists of the word "Sika" in a bold, italicized, sans-serif font, with a registered trademark symbol (®) to its right. The text is white and is set against a red triangular background that points downwards.

# Construction

<b>Caution</b>	<b>IRRITANT:</b> Contains Polymer Solution (Mixture) and 2-Butoxyethanol (111-76-2). Causes eye/skin/respiratory irritation. May cause effects such as drowsiness, dizziness, decrease in motor functions. Narcosis, or other central nervous system effects. Harmful if swallowed. Deliberate misuse by inhalation of vapors may be harmful or fatal. Strictly follow all usage, handling and storage instructions.
<b>Handling and Storage</b>	Avoid direct contact. Wear personal protective equipment (chemical resistant goggles/gloves/clothing) to prevent direct contact with skin and eyes. Use only in well ventilated areas. Open doors and windows during use. Use a properly fitted NIOSH respirator if ventilation is poor. Wash thoroughly with soap and water after use. Remove contaminated clothing and launder before reuse.
<b>First Aid</b>	<b>Eyes:</b> Hold eyelids apart and flush thoroughly with water for 15 minutes. <b>Skin:</b> Remove contaminated clothing. Wash skin thoroughly for 15 minutes with soap and water. <b>Inhalation:</b> Remove to fresh air. <b>Ingestion:</b> Do not induce vomiting. Dilute with water. Contact physician. <b>In all cases contact a physician immediately if symptoms persist.</b>
<b>Clean Up</b>	Use personal protective equipment (chemical resistant gloves/ goggles/clothing). Without direct contact, remove spilled or excess product and placed in suitable sealed container. Dispose of excess product and container in accordance with applicable environmental regulations.

**KEEP CONTAINER TIGHTLY CLOSED • KEEP OUT OF REACH OF CHILDREN • NOT FOR INTERNAL CONSUMPTION • FOR INDUSTRIAL USE ONLY**

All information provided by Sika Corporation ("Sika") concerning Sika products, including but not limited to, any recommendations and advice relating to the application and use of Sika products, is given in good faith based on Sika's current experience and knowledge of its products when properly stored, handled and applied under normal conditions in accordance with Sika's instructions. In practice, the differences in materials, substrates, storage and handling conditions, actual site conditions and other factors outside of Sika's control are such that Sika assumes no liability for the provision of such information, advice, recommendations or instructions related to its products, nor shall any legal relationship be created by or arise from the provision of such information, advice, recommendations or instructions related to its products. The user of the Sika product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with the full application of the product(s). Sika reserves the right to change the properties of its products without notice. All sales of Sika product(s) are subject to its current terms and conditions of sale which are available at [www.sikacorp.com](http://www.sikacorp.com) or by calling 800-933-7452.

**Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's most current Technical Data Sheet, product label and Material Safety Data Sheet which are available online at [www.sikaconstruction.com](http://www.sikaconstruction.com) or by calling Sika's Technical Service Department at 800-933-7452. Nothing contained in any Sika materials relieves the user of the obligation to read and follow the warnings and instruction for each Sika product as set forth in the current Technical Data Sheet, product label and Material Safety Data Sheet prior to product use.**

Sika warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Technical Data Sheet if used as directed within shelf life. User determines suitability of product for intended use and assumes all risks. Buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKASHALL NOT BELIEABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKASHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Visit our website at [www.sikaconstruction.com](http://www.sikaconstruction.com)

1-800-933-SIKA NATIONWIDE

**Regional Information and Sales Centers.** For the location of your nearest Sika sales office, contact your regional center.

**Sika Corporation**  
201 Polito Avenue  
Lyndhurst, NJ 07071  
Phone: 800-933-7452  
Fax: 201-933-6225

**Sika Canada Inc.**  
601 Delmar Avenue  
Pointe Claire  
Quebec H9R 4A9  
Phone: 514-697-2610  
Fax: 514-694-2792

**Sika Mexicana S.A. de C.V.**  
Carretera Libre Celaya Km. 8.5  
Fracc. Industrial Balvanera  
Corregidora, Queretaro  
C.P. 76920  
Phone: 52 442 2385800  
Fax: 52 442 2250537



Sika and Sikagard are registered trademarks.  
Made in USA. Printed in USA.